



ARTICLE 9250 A2 TX VIS À BOIS À TÊTE PLATE POINTE CUT

ITEM 9250 A2 TX
PAN WASHER HEAD TIMBER SCREWS WITH CUTTING POINT

APPLICATIONS:

Idéale pour les vissages en extérieur, comme par exemple solaire, abri de garage, balcons, passerelles, maisons préfabriquées et toutes les constructions portantes.

Une profondeur de vissage de 4 fois le diamètre est requise. Une profondeur de vissage de 8 fois le diamètre serait l'idéal. Une profondeur de plus de 12 fois le diamètre ne doit pas être prise en compte dans les calculs.

USES:

Ideal for Outdoor screw connections such as solar equipment, car ports, balconies, steps, playground equipment, prefabricated houses and all supporting components


A minimum screw-in depth of 4x the diameter must be ensured. A screw-in depth of 8x the diameter should ideally be achieved. More than 12x the diameter must not be included in calculations.

CARACTÉRISTIQUES:

- Vis à bois à tête plate
- Pointe Cut
- revêtement de glissière spéciale
- TX entraînement à six lobes

FEATURES:

- Pan washer head timber screws
- cutting point
- Anti-Friction-coating
- TX drive



d	4	4,5	5	6	8
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
25	9250240 25/18	9250245 25/18	9250250 25/18		
30	9250240 30/18	9250245 30/18	9250250 30/20	9250260 30/20	9250280 30
35	9250240 35/24	9250245 35/24	9250250 35/24	9250260 35/24	
40	9250240 40/24	9250245 40/24	9250250 40/24	9250260 40/24	9250280 40
45	9250240 45/30	9250245 45/30	9250250 45/30	9250260 45/30	
50	9250240 50/30	9250245 50/30	9250250 50/30	9250260 50/30	9250280 50
55	9250240 55/36	9250245 55/36	9250250 55/36	9250260 55/36	
60	9250240 60/36	9250245 60/36	9250250 60/36	9250260 60/36	9250280 60/50
65	9250240 65/36	9250245 65/36	9250250 65/36	9250260 65/36	
70	9250240 70/42	9250245 70/42	9250250 70/42	9250260 70/42	9250280 70/50
80	9250240 80/48	9250245 80/48	9250250 80/48	9250260 80/48	9250280 80/72
90		9250245 90/54	9250250 90/54	9250260 90/54	9250280 90/80
100		9250245 100/60	9250250 100/60	9250260 100/70	9250280 100/80
110				9250260 110/70	9250280 110/80
120			9250250 120/70	9250260 120/70	9250280 120/80
130				9250260 130/70	9250280 130/80
140				9250260 140/70	9250280 140/80
150				9250260 150/70	9250280 150/80
160				9250260 160/70	9250280 160/80
170				9250260 170/70	9250280 170/80
180				9250260 180/70	9250280 180/80
190				9250260 190/70	9250280 190/80
200				9250260 200/70	9250280 200/80
220				9250260 220/70	9250280 220/80
225					9250280 225/80
240				9250260 240/70	9250280 240/80
250					9250280 250/80
260				9250260 260/70	9250280 260/80
280				9250260 280/70	9250280 280/80
300				9250260 300/70	9250280 300/80
320					9250280 320/80
325					9250280 325/80
340					9250280 340/80
350					9250280 350/80
360					9250280 360/80
380					9250280 380/80
400					9250280 400/80

Ø	200	200	200 ≥ 60 100	100 ≥ 200 50	100 ≥ 120 50
k	3	3,2	3,5	3,8	4,6
dk	12	13	14	15	20
Empr.	TX20	TX20	TX25	TX25	TX40

